

EFCONE ELEVATOR

Aplace where elevation become easy



Mfgrs. of:
Passenger Lift
MRL Lift
Hospital Lift
Capsule Lift
Home Lift
Goods Lift etc.

653 B/100 Sector J, Janikipuram Garden Lucknow efconelevator@gmail.com Mob.: 9918370062, 9839347019, 9795036026



We at **EFCONE ELEVATOR COMPANY** offer following type of elevator



Traction Machine Room



Home



MRL Grearless



Hospital Elevator



Goods Elevator



apsule levator



Parking




Hydraulic Elevator



Capsule Elevator

Features of the Capsule Elevators

- Made from S.S. / M.S. with vision panel.
- Color-Powder coated, Elegant looks, Light in weight and variable speed.
- Controller Full Proof to voltage (PLC or Sold state) with fully collective - selective system.
- AC VVVF drive for jerk free operation & for variable speed.
- Overload indication and Auto Door announcing system.
- Push Button Luminous type highly attractive as well as durable.
- Facility Floor Position Indication at the floors as well as in cabin.





Passenger Elevator

- ➡ EFCONE ELEVATOR COMPANY has been engineered with full automatic doors / manual doors.
- Fabricated with most advanced Lift controls, appreciated for their high speed, smooth travel & perfect leveling and different types of doors Center Opening, Telescopic Opening.
- The Passengers Elevators detailed here are designed to handle promptly and efficiently the transportation requirements of any type of building -which means any traffic condition.
- A superior combination of flexibility and performance.
- ⇒ It gives benefits of jerk less travailing, economically low power consumption and excellent design.

CAPACITY 04 TO 20 Passenger

Lift Well

Person Weight Width Depth Width Depth

1360 | 2500 | 2050 | 2000 | 1550

1088 2500 2000 1300

Manual Door

Car Inside Entrance







All Dimension are in mm.
 This is General Data, it may be changed without notice

All hoist way walls should be minimum 230 mm brick or 150 mm R.C.C.

Auto Door

Lo	oad	Lift	Well	Car I	nside	Entrance	M	achine R	loom	UP To 1	1.5 M/Sec.		TO N/Sec.
Person	Weight	Width	Depth	Width	Depth		Width	Depth	Height	Pit	O.H.	Pit	O.H.
IN	KG.	Α	В	c	D	E	F	G	н	К	М	K	M
6	408	1650	1650	1100	1000	700	3000	3500	2500	1600	4800	2600	6700
6	408	1700	1500	1100	1000	700	3000	3500	2500	1600	4800	2600	6700
8	544	1800	1800	1200	1100	800	3200	3500	2500	1600	4800	2600	6700
10	680	1900	2000	1350	1300	800	3500	4000	2500	1600	4800	2600	6700
13	884	2500	1900	2000	1100	1000	4000	4200	2500	1600	4800	2600	6700
16	1088	2500	2000	2000	1300	1000	4500	4800	2500	1600	4800	2600	6700
20	1360	2500	2300	2000	1550	1000	5000	5000	2500	1600	4800	2600	6700


- All Dimension are in mm.
 This is General Data, it may be changed without notice.
- All hoist way walls should be minimum 230 mm brick or 150 mm R.C.C.

Hoisrway Machine Room Plan

Hoistway Elevation Drawing

Floor

Pit 1600






CAPACITY 15 TO 26 Passenger

Hospital Elevator

- Bed elevators a purpose designed solutions for hospitals and renowned for fine quality and robust performance.
- A wide range of Car dimensions is available for the varying requirements of a modern hospital.
- The entire system is Safe and reliable operating Steadily.
- Features: Accurate Open and Shut Control, Stable and Smooth.





Automatic Centre Opening Door Lifts

Person	Capacity	Shaft-W	Shaft-D	Car-W	Car-D	Entrance
	Kg	Α	В	С	D	E
15	1020	1900	3000	1000	2400	800
20	1360	2300	3000	1300	2400	900
26	1768	2600	3000	1600	2400	1000

Collapsible Door can be provided if required.

Automatic Telescopic Door Lifts

Person	Capacity	Shaft-W	Shaft-D	Car-W	Car-D	Entrance
	Kg	Α	В	С	D	E
15	1020	1700	3000	1000	2400	800
20	1360	1950	3000	1300	2400	900
26	1768	2100	3000	1600	2400	1000

All dimension in mm.

GOODS ELEVATOR

- Freight means a powerful hoisting machine, durability to cope with rough treatment, a smooth ride to handle fragile loads, leveling accuracy for easy loading and unloading, and wide doors that maximize in-car space.
- Freight elevators are typically larger and capable of carrying heavier loads than a passenger elevator, generally from 500 to 4000 kg.
- Wee supply freight elevators with dust proof equipments as per our customer requirement.

Capacity	Shaft-W	Shaft-D	Car-W	Car-D	Entrance
Kgs.	(C)	(D)	(A)	(B)	(E)
500	1900	1500	1100	1200	900
1000	2300	2100	1400	1800	1150
1500	2600	2300	1700	2000	1400
2000	2600	2800	1700	2500	1400
2500	2900	2800	2000	2500	1625
3000	2900	3300	2000	3000	1625







Collapsible Door Landing



Reduction in Elevator Equipment Area of

MRL Elevator

Machine Roomless Elevator








loistway Elevation Drawing

Capacity		Car Inside		Lift Well		Clear Entrance	Clear Opening At Landing		
Person	Kgs	А	В	С	D	E	F Auto Door	F Manual Telescopic	
6	408	1200	900	1800	1400	700	780 / 2100	1450 / 2350	
8	544	1300	1100	1900	1600	800	880 / 2100	1600 / 2350	
10	680	1300	1300	1900	1800	800	880 / 2100	1600 / 2350	
13	884	1600	1400	2200	1900	900	980 / 2100	1700 / 2350	
	_	_			_				




Hoistway Plane Layout




Home Elevator

Hoistway Elevation Drawing



Main Features :

- . Is Noiseless and easy to install
- Requires a small space



RPM	120	Pulley Dia.	100 mm
Frequency	12 Hz.	Rope Dia.	4 mm
Voltage	230 VAC	No. of Ropes	4
Kw / Hp	0.75 / 1	Lifting Capacity	300 kg
Weight	70 kg.	Lift Speed	up to 0.50 m/s
Brake	Pick-up: 220 VDC	Max. Travel	15 Mts.
Voltage	Holding: 110 VDC	Starts / Day	100



Mini Gearless Machine



Hydraulic Elevator For Low Rise

Hydraulic Passenger, Goods Elevator, Manual, Autodoor for Residential, Commercial, Hotel, Clubs, Bungalows & Industrial Buildings depending upon the shaft size & convenient machine room less movement of men, material & vehicles, with speed / amenities up to choice of owners.

Guidelines:

The lift need to be operated by authorized personnel's only.

The "dead stick" type control should return to 'neutral' or 'off' position when released.

The hydraulic pressure should never exceed the recommended level



CAPACITY 03 TO 24 Passenger



It is a directly suspension with a simple or split piston. It is the simplest solution of suspension for any load. upto 6 meters travel.





Persons	Capacity Kg	Car-W (A)	Card-D (B)	Shaft-W (C)	Shaft-D (D)
3	204	800	1500	1500	1500
4	272	850	1050	1550	1550
5	340	1000	1200	1600	1600
6	408	1100	1250	1700	1700
8	544	1200	1500	1700	1800
10	680	1200	1700	1700	2000
12	844	1300	1800	1900	2100
15	1088	1300	2200	2000	2500
20	1428	1400	2500	2100	2800
24	1700	1500	2500	2200	2800





Ful Glass Door



Golden Decorative Door



S.S. Small Vision Door



S.S. Hairline Door



Collapsible Door



M.S. Swing Door



Telescopic Door



Imperforate Door

Cabin Design

EFCONE ELEVATOR







Designer Cabin





M.S. Powder Coted Cabin



Golden Hair Line Designer Cabin



Stainless Steel Designer Cabin



M.S. & Half Glass Cabin



S.S. & Glass Cabin



Embossing Designer & Glass Cabin



EFCONE ELEVATOR

A place where elevation become easy



Gearless Motor Unit



Gearless Machine



Gearless Machine

Geared Motor Unit



Heavy Duty Traction Machine

High Speed Traction M/c.

Microprocessor Control Panel



Autodoor Control Panel



Integrated Controller Panel



Microprocessor Controller



MRL Control Panel



V3F Drive